



JABS Group A/S  
Kratholmvej 27B  
DK,5260 Odense S  
Denmark

22

DoP ref. Opt2023-A3

EN 14351-1:2006 + A2:2016  
NB 1235

Windows - Type: 3 layer Optima wood-alu

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices (reversible window):	Pass
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	0,78
Radiation properties:	
- Solar factor (gg-value):	0,53
- Light transmittance (LTg-value):	0,75
Air permeability:	npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523  
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.



JABS Group A/S  
Kratholmvej 27B  
DK,5260 Odense S  
Denmark

22

DoP ref. Opt2023-A3

EN 14351-1:2006 + A2:2016  
NB 1235

External pedestrian doorset - Type: 3 layer Optima wood-alu

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Door outward opening 1230x2180 mm standard glazing:	0,84
Radiation properties:	
- Solar factor (gg-value):	0,53
- Light transmittance (LTg-value):	0,75
Air permeability:	npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523  
acc. EN 14351-1:2006+A2:2016, Tabel E.2 note d.

# Declaration of Performance

## 3 layer Optima wood-alu



Rev. DoP Opt2023-A3

The performance of the product is in conformaty with the declared performance.  
The declaration of performance is issued under the responsibility of JABS Group A/S.

On behalf of the producer:

Bo Christensen  
Managing director

Odense, 2023-11-24

Product type	Windows and external pedestrian doorset
Identification	3 layer Optima wood-alu
Intended use	Dedicated for use in residential and public buildings
Manufacturer	JABS Group A/S, Kratholmvej 27B DK,5260 Odense S, Denmark phone +45 70231523, e-mail info@jabsgroup.com
The Assessment and Verification of Constasy of Performance (AVCP):	System 3
Harmonized standard & Notified Body:	EN 14351-1:2006 A2 -2016 Windows and doors - Product standard, Performance characteristics - Part 1: windows and external pedestrian doorset
Danish Technological Institute, NB 1235 tested	
- Calculation of thermal properties	ITC report 998005
- Load bearing capacity of safety devices	Report 129215

### Declared performance:

Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices (reversible window):	Passed
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	0,78
- Door outward opening 1230x2180 mm standard glazing:	0,84
Radiation properties:	
- Solar factor (gg-value):	0,53
- Light transmittance (LTg-value):	0,75
Air permeability:	npd