

Declaration of Performance

2 layer Optima wood



DoP ref. Opt2022-F2-1

The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type:	Windows and external pedestrian doorset
Identification:	2 layer Optima wood
Intended use:	Dedicated for use in residential and public buildings
Manufacturer:	JABS Group A/S, Cortex Park Vest 3 DK,5230 Odense M, Denmark phone +45 70201887, e-mail info@jabsgroup.com
The Assessment and Verification of Constancy of Performance (AVCP):	System 3
Harmonized standard & Notified Body:	EN 14351-1:2006 A2 -2016 Windows and doors - Product standard, Performance characteristics - Part 1: windows and external pedestrian doorset
Danish Technological Institute, NB 1235	- Calculation of thermal properties: ITC report 130285 - Load bearing capacity of safety devices: Report 129215
Declared performance:	
Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices:	Passed
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window 1230x1480 mm standard glazing:	1,38
- Door outward opening 1230x2180 mm standard glazing:	1,42
Radiation properties:	
- Solar factor (gg-value):	0,73
- Light transmittance (LTg-value):	0,82
Air permeability:	npd

On behalf of the producer:

Bo Overgaard Christensen
Managing Director

Odense, 2024-08-20



JABS Group A/S
Cortex Park Vest 3
DK,5230 Odense M
Denmark

22

DoP ref. Opt2022-F2-1

EN 14351-1:2006 + A2:2016
NB 1235

Windows and external pedestrian doorset - Type: 2 layer Optima wood

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices (reversible window):	Passed
Acoustic performance:	npd

Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	1,38
- Door outward opening 1230x2180 mm standard glazing:	1,42

Radiation properties:	
- Solar factor (gg-value):	0,73
- Light transmittance (LTg-value):	0,82

Air permeability: npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70201887
acc. EN 14351-1:2006+A2:2016, Table E.1 note c. and Table E.2 note d.